



**NOTES:**

**ELECTRICAL:**

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5AMP
3. CONTACT RESISTANCE: 100MILLIOHMS MAX
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN

**ENVIRONMENTAL:**

1. STORAGE: -40° TO +85°
2. OPERATION: 0° TO 70°

**MECHANICAL:**

1. HOUSING MATERIAL: ABS White ;
2. CONTACT GOLD PLATED: IRON WITH GOLD PLATED
3. PCB MATERIAL: FR-4 T=1.6mm ;
4. HDMI JACK LIFE: 750 TIMES MIN;

Telecom & Security S.R.L.

SW	Number	Bill No. of Alteration	Signature	Date	Tolerance
Drawn			2016. 1. 14		±0.15 ±0.20 ±0.25
Checked			2016. 1. 14		±0.15 ±0.20 ±0.25
Approved			2016. 1. 14		±0.15 ±0.20 ±0.25

Material	Angles Projection	Size	Scale	Unit	Item No.	Part Name
ABS <td></td> <td>A4 <td>X:1 <td>mm <td>UK-HDMI</td> <td>HDMI Keystone Jack</td> </td></td></td>		A4 <td>X:1 <td>mm <td>UK-HDMI</td> <td>HDMI Keystone Jack</td> </td></td>	X:1 <td>mm <td>UK-HDMI</td> <td>HDMI Keystone Jack</td> </td>	mm <td>UK-HDMI</td> <td>HDMI Keystone Jack</td>	UK-HDMI	HDMI Keystone Jack
Sheet		1 OF 1	Version:	A/0	ERP	Part No.