HDMI Splitter 1 x 2

USER MANU

4 ULTRAHD

1.0 Introduction

4K HDMI splitter IX2 distributes 1 HDMI source to 2 HDMI displays simultaneously, and 3D Compatible. It offers HD solutions for HDTV retail and show site, HDTV, STB, DVD and Projector factory, noise, space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.

2.0 Specifications

| Input Video Signal | 0.5 -1.0 volts p-p |
|-----------------------|---|
| Input DDC Signal | 5 volts p-p (TTL) |
| Max Single Link Range | 4K x 2K@30Hz |
| Output Video | HDMI 1.4a + HDCP1.0/1.1/1.2/1.3 |
| Resolutions DTV/HDTV | 576i/576p/720p/1080i/1080P/4K |
| HDMI Version | HDMI 1.4 |
| Frequency Bandwidth | EDID Duration |
| EIDI Duration | 4 seconds |
| Power | from USB cable |
| Support deep color | 30bit, 36bit, 48bit per pixel |
| Digital audio format | DTS-HD/Dolby-true-HD/LPCM 7.1/ DTS/Dolby-AC3/DSD |


3.0 Connection

A) Connect the input source and output displays to the HDMI Splitter.
*Please refer to the Connection Image.

When input source and output displays are connected and turned on, the corresponding LED will light.

Attention: In order to protect the splitter and your devices, p lease make sure the splitter is powered off before you attach in or extract video source and displays. Please insert and extract HDMI cables gently.

4.0 Interface



5.0 Box Contents

| Item | Qty | Remark |
|---------------------|-------|--------|
| HDMI splitter 1 × 2 | 1 PCS | |
| USB Cable | 1 PCS | |
| User Manual | 1 PCS | en |

6.0 FAQ

A) The splitter doesn't appear to be functioning. Firstly, check if the LED lights, if the power supply is in good condition and well connected. Secondly, make sure all cables are in good condition and well connected.

Thirdly, make sure the length of the cables is within the maximum supported length of this splitter. Lastly, please try to connect the input source to the display directly to see if it display normally.

B) If the maximum resolution the two displays supported is not the same, what resolution be displayed?

The splitter will display at the lower one to both displays.

7.0 Connection

